

CANTER 616

4x2 / WIDE CAB / MANUAL or DUONIC AMT



GVM

5,995_{kg}

GCM

9,500_{kg}

Power / Torque

110_{kW} / 370_{Nm}

- 30,000km service intervals
- Car licence
- Disc brakes
- Adjustable speed limiter

SPECIFICATIONS - CANTER 616

MODEL

4X2 616 WIDE CAB 5 SP. MAN	FEB51ER4SFAC	3400 (E)	5995	9500
4X2 616 WIDE CAB 6 SP. AMT	FEB51ER3SFAC	3400 (E)	5995	9500
4X2 616 WIDE CAB 5 SP. MAN	FEB51GR4SFAC	3850 (G)	5995	9500
4X2 616 WIDE CAB 6 SP. AMT	FEB51GR3SFAC	3850(G)	5995	9500


WHEELBASE (mm)

GVM (kg)

GCM (kg)

ENGINE

Engine Version	FUSO 4P10-T4 Euro 5 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Type	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Power (DIN)	110kW @ 2840~3500rpm
Torque (DIN)	370Nm @ 1350~2840rpm
Maximum Engine Speed	4100rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled with Viscous Fan, 13.7L capacity Engine Oil Cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Cold Start Preheat	Standard
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9
Emission Level	EURO 5 (ADR 80/03) and EEV rated (Enhanced Environmentally-Friendly Vehicle)



FUEL

Injection System	Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity (L)	100
Filtration	Filter with Water Separator and Indicator Sensor

ELECTRICAL

Voltage	12V Negative Earth
Alternator Capacity	12V-110 amp
Battery Specification	Heavy Duty 115D31L x 2
Headlamp Type	Halogen 2 x 55W / 60W
Fog lamp in bumper	Standard

CLUTCH

	DUONIC AMT	Manual
Clutch Model	DUONIC Automated (no clutch pedal)	FUSO C4W30
Type	Dual Clutch (Wet Multi-plate)	Single Dry Plate, Direct Hydraulic Type, 300mm

TRANSMISSION

	DUONIC AMT	Manual
Version	FUSO DUONIC M038S6	FUSO M038S5
Type / Speeds	6 Speed Automated Manual with Auto and Manual Modes	5 Speed with In-Dash Gearshift Lever
Features	Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage	Synchromesh 2nd-5th
Ratios	1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397	1st: 5.494 2nd: 3.193 3rd: 1.689 4th: 1.000 5th: 0.723 Rev. 4.494
PTO Opening	LH Side	LH Side

FRONT AXLE

Axle	FUSO F200T "I" Beam
Design Capacity (kg)	2600
Max Operating Capacity (kg)	2570

FRONT SUSPENSION

Type	Taper leaf spring with Stabiliser Bar and Double Acting Shock Absorbers
Size (mm)	1150 x 70

REAR AXLE

Axle	FUSO D03 Full Floating Banjo
Ratio	4.875:1
Design Capacity (kg)	4500
Max Operating Capacity (kg)	4500

REAR SUSPENSION

Type	Steel Suspension
Details	Taper leaf spring with Stabiliser Bar and Double Acting Shock Absorbers
Size Main Leaves (mm)	1250 x 70

STEERING

Power Assisted	Tilt/Telescopic Adjustable Steering Wheel
----------------	---

SPECIFICATIONS - CANTER 616

BRAKES

Type	Hydraulic Dual Circuit with Front and Rear Twin Calliper Discs
Size Front/Rear (mm)	293 x 40
Features	ABS plus EBD (Electronic Brake Distribution) Exhaust Brake Brake Priority System
Park Brake	Transmission Mounted

WHEELS AND TYRES

Wheel Type	7 x Single Piece Disc Rims (Including Spare)
Wheel Size	16.0 x 5.5K-115
Wheel Stud Pattern	5 Stud 208 PCD
Tyre Size All	205/85R16
Spare Tyre Carrier	Provided

CHASSIS

Type	Reinforced Tapered Channel
Size (mm)	192 x 60 x 6
Width (mm)	750

Refer to the bodybuilders guidelines on the Fuso website (www.fuso.co.nz) before mounting a body or modifying the chassis

INSTRUMENTS

Gauges	Speedometer with Odometer Tachometer Fuel Level Water Temperature
Colour Information Display	Fuel Consumption DPF Bar Chart from 1~9 Water Temperature Maintenance Reminder System Date and Time Tripmeters x 2

STANDARD FEATURES

Airbag(s)	Drivers Air Bag and Seat Belt Pre-Tensioner
Hill Start System	Adjustable Engagement on Manual Transmissions
Speed Limiter	Activated and adjustable by dealer
Cab Cooling and Heating	Air Conditioner / Heater / Demister
Accessory Power	12V Accessory Power Outlet / Cigar Lighter
Driving	AM/FM CD + USB + AUX + Bluetooth Hands Free Keyless Central Locking Electric Windows LED Map Lamp and Fluorescent Cabin Lamp Cup Holders (2)
Storage	Dual Overhead Storage Pockets In-Dash Centre Document Storage Door Storage Pockets Lockable Glove Box Coat Hooks

STANDARD FEATURES (continued)

Cab: External	Front End-Outline Marker Lamps Front Step Lights
Chassis	Reverse Warning Buzzer

CAB FEATURES

Type	All Steel Forward Control Manual Tilt
Cab Structure	ECE-R29 European Cab Strength Approved with Door Side Impact Beams
Mounting	Hydroelastic 4 Point
Underseat Engine Access	Available on some models
Colour	Natural White (W31)
Windscreen Wipers	2 Speed + Intermittent Cycle with Integrated Washer Nozzles
Rear Vision Mirrors	1 x Internal 2 x External Convex Heated
Interior	Fully Trimmed cab with vinyl floor covering
Seating Capacity	3
Seat Belts	Driver - Height adjustable ELR 3 Point with tension reducer Outside Passenger - ELR 3 point Centre Passenger - Lap belt
Seat (driver)	Heavy Duty Suspended with LH Arm Rest, Adjustable Lumbar Support and Weight Adjustment. Cloth Trim
Seats (passenger)	Flat Folding, 2 Passenger Bench with headrest in outside position

SERVICE INTERVALS

30,000km or 12 months (whichever occurs sooner)

WARRANTY

100,000km or 36 months (whichever occurs sooner)

PERFORMANCE

	DUONIC AMT	Manual
Turning Circle (kerb to kerb - metres)	E = 11.6 G = 13.0	E = 11.6 G = 13.0
Road Speed (km/h) at Max Engine Speed	134	134
Est Engine RPM at 90km/hr	2230	2300
Gradeability at Rated GVM (theoretical)*	34%	35%
Notes	*This is theoretical performance only. Actual performance may vary under different conditions	

KERB WEIGHTS AND MAX AXLE LOADS (kg)

		Vehicle Ratings**		Max Axle Loadings**		Kerb Weights*		
		GVM	GCM	Front	Rear	Front	Rear	Total
616 Wide Cab 5 Sp. MAN	FEB51ER4SFAC	5995	9500	2570	4500	1550	695	2245
616 Wide Cab 6 Sp. AMT	FEB51ER3SFAC	5995	9500	2570	4500	1565	705	2270
616 Wide Cab 5 Sp. MAN	FEB51GR4SFAC	5995	9500	2570	4500	1550	715	2265
616 Wide Cab 6 Sp. AMT	FEB51GR3SFAC	5995	9500	2570	4500	1565	725	2290

* Weights (est.) includes 10L fuel and spare wheel and are subject to 2.5% variation (+/-)



** Vehicle ratings and max axle loadings may be limited by local regulations.

SPECIFICATIONS - CANTER 616

DIMENSIONS (mm)

	E Wheelbase	G Wheelbase
Wheelbase	3400	3850
Length Overall	5935	6685
Height Overall	2185	2185
Width Overall	1995	1995
Width Rear Axle	1935	1935

	E Wheelbase	G Wheelbase
Width Front Track	1670	1670
Width Rear Track	1495	1495
Width Frame	750	750
Height Frame at Rear Axle	783	782



Scale = 1:50 (20mm = 1 metre). This scale is accurate when used on the original spec sheet, be aware that enlarging these illustrations can alter the scale and cause incorrect measurements. Fuso New Zealand and its authorised dealers always recommend customers seek professional advice from independent sources before commencing any engineering activities.

fuso.co.nz

0800 FUSO NZ

FUSO
DELIVERING BETTER

A policy of continual improvement means that specifications detailed in this brochure are subject to change without notice. Contact your authorised Fuso dealer to confirm current specifications. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © Fuso NZ (2017)