CANTER EURO 4.0T

GVM	GCM	POWER	W/BASE	CODE
5995kg	9500kg	157ps (JIS Gross)	3400mm	FEB71ER3WFAC
5995kg	9500kg	157ps (JIS Gross)	3850mm	FEB71GR3WFAC
7500kg	11000kg	157ps (JIS Gross)	3400mm	FEB71ER3WFAC
7500kg	11000kg	157ps (JIS Gross)	3850mm	FEB71GR3WFAC



PERFORMANCE

Maximum Speed: 127 Kmh
Gradeability at Rated GVM: 31%
Turning Circle (kerb to kerb): E=12.2m, G=13.6m


ENGINE

Mitsubishi 4P10-7AT4 (Euro V)

Description: 4 Cylinder
Configuration: Inline -DOHC 4 Valve
Type: Variable Geometry Turbo Charged

with Air to Air Intercooler
Displacement: 2,998cc 95.8x104mm
Power (DIN Nett): 110kw @ 2840 to 3500rpm
Torque (DIN Nett): 370Nm @ 1350 to 2840 rpm
Compression Ratio: 17.5:1
Oil Cooler: Water Cooled

4P10-7AT6



FUEL

Pump: Bosch Common Rail
Governor: Electronic
Filtration: Main Filter with Water Separator
Fuel Capacity: 100 Litre/Lockable
Air Cleaner: Dry Paper Element/Vertical Intake

EMISSION SYSTEMS

Emission Standard: Euro V + Enhanced Environmentally Friendly

vironmentally Friendly Vehicle (EFV)

Diesel Particulate Filter (DPF) Exhaust with DPF Status on dash display

COOLING

Fan: 460mm Diameter with 9 Blades
Fan Drive: Viscous Coupling
Radiator: Corrugated Fin with expansion tank

ELECTRICAL

Voltage: 12 volt
Alternator Capacity: 110 amp
Battery Capacity: 2x12V 90 AH
Headlamp: Halogen 55/60W
Fog lamp: Front Bumper

CLUTCH

Description: Fully Automated Wet Dual Clutch

TRANSMISSION

Description:	FUSO Duonic M038S6 AMT		
No. of Speeds:		6	
Ratios:	- 1st:	5.397	
	– 2nd:	3.788	
	– 3rd:	2.310	
	– 4th:	1.474	
	- 5th:	1.000	
	- 6th:	0.701	
	– Rev:	5.397	
PTO Opening:		LHside	

PROPELLER SHAFT

Type: P3
Universal Joint: Needle Roller

FRONT AXLE

Type: Mitsubishi Reverse Elliot 'l' Beam Design Capacity: 3100kg Maximum Operating Capacity: 3100kg

REAR AXLE

Description: Mitsubishi D035H
Type: Full floating Hypoid
Design Capacity: 6000kg
Maximum Operating Capacity: 6000kg
Ratio: 5.714

STEERING

Type: Integral Power Assisted Ball
Steering Wheel: Urethane with Airbag
Steering Column: Tilt/Telescopic Adj

BRAKES

Type: Hydraulic Dual Circuit with ABS/EBD.
Dual Caliper Ventilated Disc Front and Rear
Brake Override safety system
Size: F 252 x 40mm, R 252 x 40mm
Park Brake: Transmission Mounted
Auxiliary: Exhaust Brake

FRONT SUSPENSION

Type: Semi-Elliptic Leaf Springs with Shock Absorbers & Stabilizer
Size: 1150x70x10-3leaf, 11-2leaf

REAR SUSPENSION

Type: Semi–Elliptic Leaf Springs with Shock Absorbers & Stabilizer Size: $1250 \times 70 \times 10 - 2 \text{ leaf} \\ 12 - 1, 10 - 3 \\ \text{Auxiliary:} \\ 880 \times 70 \times 15 - 3 \text{ leaf}$

CHASSIS

 Type:
 Reinforced Taper Channel

 Size:
 192×60×6mm

 Width:
 752mm

 Tensile Strength:
 440 mpa

WHEELS & TYRES

Wheel Type: Single piece tubeless rims
Wheel Size: 17.5"
Tyre Size: 215/75R17.5
Spare & Tyre Carrier: YES



KERB WEIGHT (kg - estimated)

	E2	G2
Front:	1750	1775
Rear:	900	900
Total:	2650	2675

Includes coolant, oils and 20 litres fuel.

DIMENSIONS (mm)		
	E2	G2
Wheel Base:	3400	3850
Overall Length:	5935	6685
Cab to Axle:	1821	2270
Rear Overhang:	1395	1695
Overall Height:	2225	2225
Overall Width:	1995	1995
Track Front:	1675	1675
Track Rear:	1560	1560

CAB FEATURES

All Steel Forward Control. ECE R29 Safety Cab

Fixed Double Cab Type: Mounting: Hydroelastic 4 point Colour: White W31 Interior: Fully Trimmed Windscreen: Laminated and Tinted 2 Speed-Intermittent with Windscreen Wipers:

Integrated Washer Nozzles 1 Internal

Rear Vision Mirrors: 2 x External Convex-Heated

Seating Capacity:

Seat Belts: Driver - Height adjustable

3 point ELR with tension reducer

Front Passenger - ELR 3 point, Centre: 2 Point Rear Passenger - Outer position: ELR 3 point

Centre: 2 point

Driver Seat: Suspension base, Fabric trim with built in headrest, lumbar support and armrest Passenger Seat: Flat folding 2 passenger bench type with left-hand headrest and fabric trim

RearSeats: Bench type, 4 person, fabric Headrest right and left sides

INSTRUMENTS

Gauges:

- Speedo with Odometer and Dual Trip Meter
- Tachometer
- Fuel Level

Warning Lights:

- High Beam
- Turn signal/Hazard warning
- Park Brake
- Exhaust Brake
- Engine Pre-Heat
- Alternator
- Low Oil Pressure
- SRS Airbag
- Brake Pad Wear
- Immobilizer
- Seat Belts
- DPF
- AMT Oil Temp
- AMT Fault

SWITCHES

- Fog Lamps
- Fluorescent Cab Lamp
- Heated Exterior Mirrors
- DPF Regeneration switch
- Transmission Economy Mode Switch
- Hazard Lights




CAB EQUIPMENT


- Driver's & front passenger airbag
- Electric Windows with one touch drivers
- Keyless Central Locking
- Door side impact beams
- Tinted side and rear glass
- Heater-Demister/Air-conditioning
- Interior sunvisors LH/RH
- AM/FM CD radio with 2 speakers
- Fluorescent Cabin Lamp
- Interior Front & Rear Dome Lamp with Delay Function
- Front Step lamps
- Cab Front Outline Marker Lights
- Cigar Lighter
- Electric Horn
- Reverse Warning Buzzer
- Tool Kit
- Overhead Parcel Shelves LH/RH
- Lower Dash Document Holder
- Engine access panel


MULTI FUNCTION DISPLAY

- Calendar/Time
- Meter and Gauge Illumination
- Service Reminders
- DPF Level indication
- Fuel Consumption Indication
- Diagnostic Trouble Code Indication
- Coolant Temperature Gauge
- Gear Position Indicator
- Odo and Dual trip meter

CANTER EURO 4.0t







CHASS[S CAB ORAW J NGS

FEB71GR3WFAC

UNJT:mm SCALE: 1/25