FIGHTER 250



GVM	GCM	POWER	W/BASE	CODE
10,600kg	20,000kg	250ps	4,870mm	FK61FK1RFAC

PERFORMANCE

Maximum Speed: 123 km/h Gradeability at Rated GVM: 54.0% Gradeability at Rated GCM: 25.5% Turning Circle (kerb to kerb): 15.6m

ENGINE

Model: Mitsubishi FUSO 6M60-9AT1 Diesel (Euro V)

Configuration: 6 cyl. In-lineOHC, 4-valve Turbocharged with air to air Intercooler; Type: PCV & common rail fuel system, SCR after-treatment system (BlueTec)


Displacement: Bore: 118mm Stroke: 115mm Power (JIS Gross): 184kw (250 ps) @ 2,500 rpm Torque (JIS Gross):

761Nm (561 lb/ft) @ 1400 rpm

2.900 rpm Maximum Engine Speed: 16:0:1 Compression Ratio Oil Cooler: Plate type, water cooled Air Cleaner: Dual element cyclonic with vertical,

intake & air restriction indicator

6M60-9AT1 ENGINE MODEL



FUEL

Injection System: DENSO common rail system Governor: Electronic Fuel Tank: 200 Litres Rectangular with Lockable Cap Fuel Cooler: Fitted

AdBlue Exhaust Fluid Capacity:

COOLING

540mm dia 10 blades Fan Drive: Thermo modulated Radiator: Corrugated fin with expansion tank

ELECTRICAL

24V negative earth Voltage: 24V-80 amp Alternator Capacity: 24V-5.0kW Starter Capacity: Battery Capacity: Heavy duty 2x12V, 100Ah/20hr Headlamp - Type: Halogen Low beam 2 x 70W - Capacity:

High beam 2 x 75W

CLUTCH

Model: C7M38 Disc Diameter: 380mm Single dry plate Type: Operation: Air assisted hydraulic Facing Area: Cerametallic - 754cm²

TRANSMISSION

Model:	M070S6-0D
No. of Speeds:	6 with air assisted gearshift
Synchromesh:	2nd-6th
1:	6.807
2:	4.172
3:	2.396
4:	1.504
5:	1.000
6:	0.774
Reverse:	6.807
PTO Opening:	LH side

PROPELLER SHAFT

Туре: P10 Universal Joint: Needle roller

FRONT AXLE

Model:	F400T
Type:	Reverse Elliot 'I' beam
Design Capacity:	3,800kg
Maximum Operating Capaci	ty: 3,800kg

REAR AXLE

25 litres

Model:	R052T
Туре:	Full floating hypoid
Design Capacity:	9,500kg
Maximum Operating Capacity:	7,000kg
Ratio:	4.444:1

STEERING

Integral power assisted – ball & nut Steering Wheel: Airbag Steering Column: Tilt/telescopic adjustable with lock

BRAKES

Туре: Air actuated hydraulic dual circuit with auto adjust, EZGO hill start assist & ABS Size: 320 x 120mm 320 x 140mm Rear: Park Brake: Rear wheel spring actuated Auxiliary: Exhaust brake Compressor: Water cooled, 340cc single cylinder

with air dryer

FRONT SUSPENSION

Parabolic leaf with stabilizer bar Type: 1,300 x 70 x 16mm – 1 leaf Size: x 18mm – 2 leaves Capacity at Ground: 2,205kg each Shock Absorbers: Double acting

REAR SUSPENSION

Type: Semi-elliptic leaf with stabilizer bar Size: 1,300 x 70 x 11mm – 9 leaves Auxiliary: 900 x 70 x 10mm – 7 leaves Capacity at Ground: 3,500kg each

CHASSIS

Parallel channel Type: Size. 228 x 80 x 7 0mm Width: 842mm Tensile Strength: 540Mpa



WHEELS & TYRES

 Wheel:
 Type:
 6 x Single piece disc

 Size:
 17.5 x 6.75-131

 Stud pattern:
 6 x 222.25mm PCD

 Tyre:
 Size:
 235/75R17.5LT 132/130M

KERB WEIGHT (kg - estimated)

Front:			2,230kg
Rear:			1,320kg
Total:			3,550kg

Includes coolant, oils, tools and 20 litres fuel.

CAB FEATURES

All steel forward control

Manual tilt 44 deg Type: Mounting: Hydroelastic susp 4 point Colour: Natural White Fully trimmed with vinyl floor mat Interior: Laminated tinted Windscreen: Windscreen Wipers: 2 Speed + Intermittent Cycle with Integrated Washer Nozzles Door: 90 degree opening angle Steering Column: Telescopic & Tilt Rear Vision Mirrors: Remote / heated with Convex Spotter (both sides)

Seating Capacity: 3
Seat Belts: 2 ELR lap sash, 1 lap with pre-tensioners
Seats: Driver: ISRI air suspension with auto levelling,
height, tilt and dampening adjustment
Integral headrest & fabric trim
Centre: Low back with fabric trim &
forward folding

LH: Fixed base, reclining, integral headrest & fabric trim

STANDARD FEATURES

Safety

- ABS
- Driver's Air Bag
- Seat Belt Pre-tensioners
- LH Transom Window
- Reverse Warning Buzzer
- Heated and remote controlled exterior mirrors
- EZGO Hill Start Assist

Driving

- Keyless Central Locking
- Electric Windows
- Cruise Control
- 24V Accessory Power Outlet/Cigar Lighter
- Air Conditioner/Heater/Demister
- Radio/CD Player/AUX/Bluetooth/Audio
 Streaming
- Cup Holders (4)
- Rear Quarter Glass
- Fluorescent Cabin Lamp and Interior Reading Lamps
- Engine Idle Speed Control

Storage

- Centre Seat Storage Console
- LH Seat Storage Tray
- Rear Bunk Storage Pocket
- Dash Storage Tray 2 DIN Glove Compartment
- 1 Single & 1 Double DIN Slot for Accessories
- Overhead Storage Pocket with Lid
- RH Door Storage Pocket

Cab External

- Roof Mounting Points (max. static load 70kg)
- Front End-Outline Marker Lamps

Chassis

– Tool Kit & Chassis Mounted Tool Box

INSTRUMENTS

Gauges:

- Speedo with Odometer
- Tachometer
- Air pressure (2)
- Fuel level & urea level
- Water temperature

Colour Information Display:

- Fuel consumption
- Service indicators
- Hour meter and tripmeter

Warning Lamps:

- Glow plug indicator
- ABS
- Turn signal
- High beam
- Exhaust brake
- Oil level
- AdBlue low
- Fuel low
- Park brake
- Alternator
- Oil filter blockage
- Engine control/cruise control (ECU)
- Air filter restriction
- Door opening
- Cab tilt lock

Warning Lamp/Buzzer:

- Air pressure
- Oil pressure
- Engine overheat/low coolant level

10.5 Chassis cab drawings

