



STATEMENT OF COMPLIANCE (FUSO New Zealand Feb 22

BRAKE & WHEELBASE COMPLIANCE INFORMATION - FUSO HD EURO 5

Fuso New Zealand confirm that the following Fuso HD trucks sold new in New Zealand, will continue to meet the specified brake standard within the allowed wheelbase range and tyre size stipulated below.

Please Note the following limitations:

- These models have a OEM fitted trailer brake system. including tractor protection and are fitted with an air brake coupling complying with HVBR requirements.
- Trailer brake valves of rigid trucks are located at the 2nd crossmember and shall not be repositioned in case of the wheelbase modification
- Trailer brake valve for FV54SJ tractor is located at the rear of the chassis and shall not be repositioned when doing a wheelbase modification.

Factory Model Code	Local Model Code	Brake Standard	Wheelbase mm (first axle to centerline of rear axle/s)		Tyre size		Application
			Standard	Modification range	Standard range	Modification range	
HD Euro 5			Standard	Modification range	Standard range	Modification range	
FP54SG	FP1641 FP410G	ADR35/01	3800	N/A	295/80R22.5 11R22.5 275/70R22.5	295/80R22.5 11R22.5 275/70R22.5	Rigid & Tractor
FV51SK	FV2541, FV2547, FV410K, FV470K		4300	4300 - 6380			
FV54SK	FV2447, FV470K		6380				
FV54ST	FV2441, FV410T		3860	3860 - 4640			
FV54SJ	FV2447, FV470J		5870	5870			
FS52SS	FS3141, FS3147, FS410S, FS470S		5900	N/A			
FS54SS	FS3147, FS470S						

Ian Porter
Product Planning Manager, Fuso New Zealand Limited