# **FUSO HEAVY**

Inline 6 Cylinder





#### **PERFORMANCE**

Maximum Speed: 117 km/hr 100km/hr speed limiter available Gradeability at Rated GCM: 24% Turning Radius (kerb to kerb): 10.3 m

#### **ENGINE**

Configuration:

#### Fuso OM457-T3 12L (Euro V)


Type: OHV, 4 Valve, Waste Gate Turbo with Intercooler Displacement: 11967cc 128mm x 155mm Bore x Stroke 295kW @ 1900rpm Power (DIN nett): (JIS Gross: 410ps\*)

Torque (DIN nett): 2000Nm @ 1100rpm (JIS Gross: 1495lb/ft\*)

Maximum Engine Speed: 2200rpm Compression Ratio: 18.5:1

\* Calculated

#### **OM457 ENGINE PERFORMANCE**



#### **FUEL**

Pump: **Bosch Unit Injectors** Governor: Electronic Main filter with water separator Filtration: Fuel Capacity: 400L Alloy tank with lockable cap RHS snorkel with single element Air Cleaner: and electronic dust indicator Cold Start Preheat: Standard

#### **EMISSION SYSTEM**

**Emission Standard** Furo V Box muffler LHS. Exhaust with BLUETEC® SCR After Treatment System. 40L ADBLUE tank with on dash gauge.

#### COOLING

Fan: 750mm diameter with 8 Blade Fan Drive Viscous Clutch Radiator: Aluminium

#### **ELECTRICAL**

Voltage: 24 volt neg earth Alternator Capacity: 24v - 80 amp Heavy Duty Batteries Capacity: 2 x 12v, 150Ah/20hr

#### CLUTCH

**Description:** C12W43P Single dry plate 430mm Type: Woven facing material

Fully Automated with Hill Start Assist Operation:

#### **TRANSMISSION**

Model:	FUSO INOMAT II G230-12 AMT			
	(2 Pedal Type)			
No. of Speeds:		12		
Ratios:	– 1st:	11.672		
	– 2nd:	9.101		
	– 3rd:	7.055		
	– 4th:	5.501		
	– 5th:	4.400		
	– 6th:	3.430		
	– 7th:	2.652		
	– 8th:	2.068		
	– 9th:	1.603		
	– 10th:	1.250		
	– 11th:	1.000		
	– 12th:	0.779		
Reverse:	High: 9.101:1	Low: 11.672:1		
Control: INOM	AT II Automated shif	t with auto and		

manual shift modes and Hill Start Assist Additional Modes: Start gear select, Slow

Manoeuvre, Economy, Reverse high/low Oil Cooler: T/M oil cooler (air cooling type)

PTO Opening: LHS and Rear mounting

# PROPELLER SHAFT

Main: P152 Type: Interaxle: P12

# **FRONT AXLE**

F900T 7,100kg Maximum Operating Capacity: (Subject to suitable tyres & certification

#### **REAR AXLE**

Description: D10HT/D10H with Interaxle diff lock Type: Single Reduction Hypoid 21600kg Design Capacity: 18000kg Maximum Operating Capacity: 4.625 Ratio:

#### **STEERING**

Type: Integral Power Assisted ball & nut Steering Wheel: Urethane with air bag Steering Column: Tilt & Telescopic adjust

#### **BRAKES**

Full air taper roller drum brakes Type: with auto adjust ABS & ASR Traction control Size: F 410 x 150mm R 410 x 200mm Park Brake: Spring on both rear axles Engine Brake: 4 stage Powertard with Exhaust Brake and Shift Down 320ps @ 2300 rpm Retardation Power: Compressor: 636cc with air dryer Air Tanks: Alloy

# **FRONT SUSPENSION**

Type: Long Taper Leaf 1500 x 90 x 23mm - 3 Size: Capacity at Ground: 7280kg Shock Absorbers: Double Acting

# **ELECTRICAL**

FUSO airbag with underslung arm Type: Size: 250mm diameter bags Trailing leaf 995 x 80 x 35mm - 2 22,500kg Capacity at Ground:

Shock Absorbers: Double acting front and rear

#### **CHASSIS**

Super Frame parallel channel Type: 300 x 90 x 7mm Size: Width: 840mm Tensile Strength: 540MPa



#### **WHEELS & TYRES**

Wheel Type: Steel Wheel Size: 8.25 x 22.5 - 165-13T Wheel Stud Pattern: 10 Stud ISO Tyre Size: Front 295/85R 22.5 & Rear: 11R22.5 Spare Tyre:

#### KERB WEIGHT (KG - ESTIMATED)

Front:			4585
Rear:			3790
Total:			8375
rotal.			83/3

Includes coolant, oils and 20 litres fuel.

DIMENSIONS (MM)	
Wheel Base:	6380
Overall Length:	11320
Cab to Axle:	5680
Rear Overhang:	3570
Overall Height:	3330
Overall Width:	2490

#### **OPTIONAL EQUIPMENT**

- 4.222 + 275/70R22.5 LP Spec

#### **MULTI FUNCTION DISPLAY**

- Calendar/Time
- Service Reminders
- Snow Mode Low speed manouvering
- Fuel Consumption Indication
- Diagnostic Trouble Code Indication
- Gear Position Indicator
- Odo and Dual trip meter
- Engine Oil level check
- Warning/indicator display
- AdBlue level indicator
- Hour Meter
- Maintenance Indicator

#### **CAB FEATURES**

Construction: All Steel Forward Control Type: Electric/Hydraulic 50 deg cab tilt Mounting: 4 Point air suspension Colour: Natural White (W31) Safety features: 90 degree opening doors with side intrusion bars Lighting: Halogen headlamps

with fog lights in bumper Interior: Fully trimmed with rear mattress Windscreen: Laminated & tinted

Windscreen Wipers: 3 windscreen wipers with built in nozzles: 2 speed & intermittent

Rear Vision Mirrors: Remote control & heated flat main mirror with heated convex spotter

Seating Capacity:

Seats: Driver: ISRI air suspension with auto levelling,

height, tilt and dampening adjustment Integral headrest & fabric trim

Passenger: Single seat, fixed base, headrest & fabric trim

Seat belts: Pretensioner, ELR attached

3 points type, centre lap belt

#### **INSTRUMENTS**

#### Gauges:

- Speedo with odometer and dual trip meter
- Tachometer
- Fuel level
- Dual air pressure gauge
- Water temperature meter

#### Warning Lamps:

- Park Brake
- Exhaust Brake/powertard
- Alternator
- Low Oil Pressure/Oil Filter Blockage
- SRS Air Bag & Seat belt
- AMT oil temp
- Engine check light
- Interaxle Diff Lock
- Brake air pressure
- Cold start indicator

- Door Open
- Low coolant level
- Cab tilt indicator
- Air filter restriction
- Cruise Control
- ABS/ASR

## **CAB EQUIPMENT**

#### Exterior:


- Lift-up front maintenance panel
- Transom window on LH door
- Roof spoiler mounting points (max weight 50kg)
- Roof mounted white marker lights x2

#### Interior:

- Fully trimmed
- Driver's air bag and seat belt pretensioner
- Large centre floor console with glove box
- Cup holder for driver
- Large overhead console boxes
- Sun visors x 2
- Interior rear view mirror
- Opening rear quarter windows
- Grab handle on 'A' pillar
- Auto air conditioning with heater/demister
- Central locking and Keyless Entry System
- Power windows and Driver's auto up/down
- 6" Touch screen audio with Bluetooth, USB and DVD player with 2nd screen output.
- Engine idle speed control
- Cruise control
- Cold start switch
- Trailer brake hand control
- Hazard warning switch
- Reading lamps
- Tool kit & jack
- Electric Horn
- Fluorescent Cab Lamp

### **FUSO HEAVY**

# 6X4 FV410T1



# 10.5 Chassis cab drawings

FV54ST3VFAC

# FV410T1

