

STATEMENT OF COMPLIANCE (FUSO New Zealand)

Jan-22

BRAKE & WHEELBASE COMPLIANCE INFORMATION - FUSO SHOGUN EURO 6 with ESC

Fuso New Zealand confirms that the following FUSO SHOGUN Euro 6 models equipped with Electronic Stability Control (ESC/EBS) sold new in New Zealand will continue to meet the specified brake standard when the wheelbase is adjusted, provided the wheelbase adjustment is to a wheelbase specified as permissible for the model listed below.

IMPORTANT:

- Vehicles subject to wheelbase adjustments or tyre changes must have authorised FUSO dealer documentation confirming the vehicles ECU has been reprogrammed prior to issuing an LT400.
- Trailer brake valves of rigid trucks are located at the second crossmember and shall not be repositioned in case of the wheelbase modification.
- Trailer brake valve for FV74HJR tractor is located at the rear of the chassis and shall not be repositioned when doing a wheelbase modification.
- The yaw sensor on the inner chassis rail must remain in the original position and orientation.
- The below vehicles have OEM fitted trailer brake system ,including tractor protection and are fitted with a air brake coupling complying with HVBR ,
- Green boxes are approved optional wheelbase settings.

Factory Model Code	Local Model Code	Brake Standard	Permissible Wheelbases mm (First axle to centre of drive axles)										Tyre size		Application			
			Standard	G	J	K	M	N	P	R	S	T	V	Standard Range		Modification Range		
			FP74HGR	FP1640	ADR35/05	3800	STD											
FV74HJR	FV2446	3910		STD		Option												
FV74VJR	FV2651	3910		STD														
FV70HK	FV2540, FV2546	4300				STD	Option	Option	Option	Option								
FV74HK	FV2446	4300				STD	Option	Option	Option	Option								
FV74VK	FV2651	4300				STD												
FV74HT	FV2440	6380						Option	Option	Option	Option	STD						
FS72HS FS74/76HS	FS3140, FS3146	5870										STD		Option				
FS74/76HV	FS3146	6720										Option		STD				



Ian Porter
Product Planning Manager Fuso New Zealand Limited